



®

ZRZR

IT'S MORE THAN QUALITY...!
TELLS ABOUT QUALITY ...!



**AUTOMOTIVE
& INDUSTRIAL
LUBRICANTS OILS
& GREASE
SOLUTION**



PRODUCT DESCRIPTION

RZR Z1 POWER PLUS 4T oil is a high performance multi grade and mineral based engine oil specially formulated for all fleet of diesel engine requiring API SN/JASO MA2 Grade its designed for modern diesel engine operating under sever conditions and heavy loads with superb cold start protect on therefore reduces engine wear & tear significantly. The special additives contribute to a significant reductions in engine noise.

Performance level

Meet API SN/JASO MA2 STANDARDS

PRODUCT BENEFITS

- ◆ Provided excellent engine clean in all service conditions.
- ◆ Excellent oxidation & stability to prolong engine oil life.
- ◆ Excellent high sheet temperature stability.
- ◆ Excellent protection against wear and tear
- ◆ Recommended for fleet of diesel engine that coupled with EGR SYSTEM and common raid system for commercial road transport.

TYPICAL APPLICATIONS

RZR Z1POWER PLUS 4T is recommended for all types of general applications of automotive and 4STROKE purposes Hero, Honda, Tvs, Bajaj, Yamaha, etc bike segments

KEY FEATURES

1. High water resistance and give excellent service in application where water ingress is unavoidable.
2. High load caring ability
3. Protection against rust and corrosion.

TYPICAL PROPERTIES

| NO | Test parameters | ASTM METHOD |
|----|---------------------------------|-------------|
| 1 | KINEMATIC VISCOSITY SCT @ 100°C | 10.5 |
| 2 | KINEMATIC VISCOSITY SCT @ 40°C | 63.5 |
| 3 | VISCOSITY INDEX (MIN) | 145 |
| 4 | FLASH POINT °C (MIN) | 210 |
| 5 | POUR POINT °C (MAX) | -10 |
| 6 | DENSITY | 0.863 |
| 7 | TBN -MG KOH/GM | 7.5 -8.5 |

PRECAUTIONS

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained





PRODUCT DESCRIPTION

RZR Z1 POWER PLUS 4T oil is a high performance multi grade and mineral based engine oil specially formulated for all fleet of diesel engine requiring API SN/JASO MA2 Grade its designed for modern diesel engine operating under sever conditions and heavy loads with superb cold start protect on therefore reduces engine wear & tear significantly. The special additives contribute to a significant reductions in engine noise.

Performance level

Meet API SN/JASO MA2 STANDARDS

PRODUCT BENEFITS

- ◆ Provided excellent engine clean in all service conditions.
- ◆ Excellent oxidation & stability to prolong engine oil life.
- ◆ Excellent high sheet temperature stability.
- ◆ Excellent protection against wear and tear
- ◆ Recommended for fleet of diesel engine that coupled with EGR SYSTEM and common raid system for commercial road transport.

TYPICAL APPLICATIONS

RZR Z1 POWER PLUS is recommended for all types of general applications of automotive and 4STROKE purposes Hero, Honda, Tvs, Bajaj, Yamaha, etc bike segments

KEY FEATURES

1. High water resistance and give excellent service in application where water ingress is unavoidable.
2. High load caring ability
3. Protection against rust and corrosion.

TYPICAL PROPERTIES

| NO | Test parameters | ASTM METHOD |
|----|--|-------------|
| 1 | KINEMATIC VISCOSITY _{SCT} @ 100°C | 15-16 |
| 2 | KINEMATIC VISCOSITY _{SCT} @ 40°C | 125 |
| 3 | VISCOSITY INDEX (MIN) | 126 |
| 4 | FLASH POINT °C(MIN) | 220 |
| 5 | POUR POINT °C(MAX) | -10 |
| 6 | DENSITY | 0.879 |
| 7 | TBN -MG KOH/GM | 7.5 -8.5 |

PRECAUTIONS

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained



PACKING SIZE : 210 LTR, 55LTR, 20LTR, 10LTR, 7.5LTR, 5LTR, 1LTR



PRODUCT DESCRIPTION

RZR RX ULTRA PREMIUM oil is a high performance multi grade and mineral based engine oil specially formulated for all fleet of diesel engine requiring API SN/JASO MA2 Grade its designed for modern diesel engine operating under sever conditions and heavy loads with superb cold start protect on therefore reduces engine wear & tear significantly. The special additives contribute to a significant reductions in engine noise.

Performance level

Meet API SN/JASO MA2 STANDARDS

PRODUCT BENEFITS

- ◆ Provided excellent engine clean in all service conditions.
- ◆ Excellent oxidation & stability to prolong engine oil life.
- ◆ Excellent high sheet temperature stability.
- ◆ Excellent protection against wear and tear
- ◆ Recommended for fleet of diesel engine that coupled with EGR SYSTEM and common raid system for commercial road transport.

TYPICAL APPLICATIONS

RZR RX ULTRA PREMIUM is recommended for all types of general applications of automotive and 4STROKE purposes Hero, Honda, Tvs, Bajaj, Yamaha, etc bike segments

KEY FEATURES

1. High water resistance and give excellent service in application where water ingress is unavoidable.
2. High load caring ability
3. Protection against rust and corrosion.

TYPICAL PROPERTIES

| NO | Test parameters | ASTM METHOD |
|----|--|-------------|
| 1 | KINEMATIC VISCOSITY _{SCT} @ 100°C | 15-16 |
| 2 | KINEMATIC VISCOSITY _{SCT} @ 40°C | 125 |
| 3 | VISCOSITY INDEX (MIN) | 126 |
| 4 | FLASH POINT °C (MIN) | 220 |
| 5 | POUR POINT °C (MAX) | -10 |
| 6 | DENSITY | 0.879 |
| 7 | TBN - MG KOH/GM | 7.5 -8.5 |

PRECAUTIONS

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained





PRODUCT DESCRIPTION

RZR RX ULTRA PREMIUM oil is a high performance multi grade and mineral based engine oil specially formulated for all fleet of diesel engine requiring API SN/JASO MA2 Grade its designed for modern diesel engine operating under sever conditions and heavy loads with superb cold start protection therefore reduces engine wear & tear significantly. The special additives contribute to a significant reductions in engine noise.

Performance level

Meet API SN/JASO MA2 STANDARDS

PRODUCT BENEFITS

- ♦ Provided excellent engine clean in all service conditions.
- ♦ Excellent oxidation & stability to prolong engine oil life.
- ♦ Excellent high sheet temperature stability.
- ♦ Excellent protection against wear and tear
- ♦ Recommended for fleet of diesel engine that coupled with EGR SYSTEM and common raid system for commercial road transport.

TYPICAL APPLICATIONS

RZR RX ULTRA PREMIUM is recommended for all types of general applications of automotive and 4STROKE purposes Hero, Honda, Tvs, Bajaj, Yamaha, etc bike segments

KEY FEATURES

1. High water resistance and give excellent service in application where water ingress is unavoidable.
2. High load caring ability
3. Protection against rust and corrosion.

TYPICAL PROPERTIES

| NO | Test parameters | ASTM METHOD |
|----|--|-------------|
| 1 | KINEMATIC VISCOSITY _{SCT} @ 100°C | 15-16 |
| 2 | KINEMATIC VISCOSITY _{SCT} @ 40°C | 125 |
| 3 | VISCOSITY INDEX (MIN) | 126 |
| 4 | FLASH POINT °C(MIN) | 220 |
| 5 | POUR POINT °C(MAX) | -10 |
| 6 | DENSITY | 0.879 |
| 7 | TBN -MG KOH/GM | 7.5 -8.5 |

PRECAUTIONS

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained





PRODUCT DESCRIPTION

RZR RX ULTRA PREMIUM oil is a high performance multi grade and mineral based engine oil specially formulated for all fleet of diesel engine requiring API SN/JASO MA2 Grade its designed for modern diesel engine operating under sever conditions and heavy loads with superb cold start protection therefore reduces engine wear & tear significantly. The special additives contribute to a significant reductions in engine noise.

Performance level

Meet API SN/JASO MA2 STANDARDS

PRODUCT BENEFITS

- ◆ Provided excellent engine clean in all service conditions.
- ◆ Excellent oxidation & stability to prolong engine oil life.
- ◆ Excellent high sheet temperature stability.
- ◆ Excellent protection against wear and tear
- ◆ Recommended for fleet of diesel engine that coupled with EGR SYSTEM and common raid system for commercial road transport.

TYPICAL APPLICATIONS

RZR RX ULTRA PREMIUM is recommended for all types of general applications of automotive and 4STROKE purposes Hero, Honda, Tvs, Bajaj, Yamaha, etc bike segments

KEY FEATURES

1. High water resistance and give excellent service in application where water ingress is unavoidable.
2. High load caring ability
3. Protection against rust and corrosion.

TYPICAL PROPERTIES

| NO | Test parameters | ASTM METHOD |
|----|--|-------------|
| 1 | KINEMATIC VISCOSITY _{SCT} @ 100°C | 15-16 |
| 2 | KINEMATIC VISCOSITY _{SCT} @ 40°C | 125 |
| 3 | VISCOSITY INDEX (MIN) | 126 |
| 4 | FLASH POINT °C(MIN) | 220 |
| 5 | POUR POINT °C(MAX) | -10 |
| 6 | DENSITY | 0.879 |
| 7 | TBN -MG KOH/GM | 7.5 -8.5 |

PRECAUTIONS

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained





PRODUCT DESCRIPTION

RZR XP POWER RACING 1 4T oil is a high performance multi grade and mineral based engine oil specially formulated for all fleet of diesel engine requiring API SL/JASO MA2 Grade its designed for modern diesel engine operating under sever conditions and heavy loads with superb cold start protect on therefore reduces engine wear & tear significantly. The special additives contribute to a significant reductions in engine noise.

Performance level

Meet API SL/JASO MA2 STANDARDS

PRODUCT BENEFITS

- ◆ Provided excellent engine clean in all service conditions.
- ◆ Excellent oxidation & stability to prolong engine oil life.
- ◆ Excellent high sheet temperature stability.
- ◆ Excellent protection against wear and tear
- ◆ Recommended for fleet of diesel engine that coupled with EGR SYSTEM and common raid system for commercial road transport.

TYPICAL APPLICATIONS

RZR XP POWER RACING 1 4T is recommended for all types of general applications of automotive and 4STROKE purposes Hero, Honda, Tvs, Bajaj, Yamaha, etc bike segments

KEY FEATURES

1. High water resistance and give excellent service in application where water ingress is unavoidable.
2. High load caring ability
3. Protection against rust and corrosion.

TYPICAL PROPERTIES

| NO | Test parameters | ASTM METHOD |
|----|--|-------------|
| 1 | KINEMATIC VISCOSITY _{SCT} @ 100°C | 18.6 -19 |
| 2 | KINEMATIC VISCOSITY _{SCT} @ 40°C | 169 |
| 3 | VISCOSITY INDEX (MIN) | 125 |
| 4 | FLASH POINT °C(MIN) | 220 |
| 5 | POUR POINT °C(MAX) | -10 |
| 6 | DENSITY | 0.885 |
| 7 | TBN -MG KOH/GM | 7.5 -8.5 |

PRECAUTIONS

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained



PACKING SIZE : 900ML, 1L, 1.2L, 5L, 7.5L, 18L, 50L, 210L



PRODUCT DESCRIPTION

RZR XTRA POWER 4T oil is a high performance multi grade and mineral based engine oil specially formulated for all fleet of diesel engine requiring API SL/JASO MA2 Grade its designed for modern diesel engine operating under sever conditions and heavy loads with superb cold start protect on therefore reduces engine wear & tear significantly. The special additives contribute to a significant reductions in engine noise.

Performance level

Meet API SN/JASO MA2 STANDARDS

PRODUCT BENEFITS

- ◆ Provided excellent engine clean in all service conditions.
- ◆ Excellent oxidation & stability to prolong engine oil life.
- ◆ Excellent high sheet temperature stability.
- ◆ Excellent protection against wear and tear
- ◆ Recommended for fleet of diesel engine that coupled with EGR SYSTEM and common raid system for commercial road transport.

TYPICAL APPLICATIONS

RZR XTRA POWER 4T is recommended for all types of general applications of automotive and 4STROKE purposes Hero, Honda, Tvs, Bajaj, Yamaha, etc bike segments

KEY FEATURES

1. High water resistance and give excellent service in application where water ingress is unavoidable.
2. High load caring ability
3. Protection against rust and corrosion.

TYPICAL PROPERTIES

| NO | Test parameters | ASTM METHOD |
|----|---------------------------------|-------------|
| 1 | KINEMATIC VISCOSITY SCT @ 100°C | 14.0-15.5 |
| 2 | KINEMATIC VISCOSITY SCT @ 40°C | 124.5 |
| 3 | VISCOSITY INDEX (MIN) | 125 |
| 4 | FLASH POINT °C (MIN) | 220 |
| 5 | POUR POINT °C (MAX) | -24 |
| 6 | DENSITY | 0.885 |
| 7 | TBN -MG KOH/GM | 7.5 -8.5 |

PRECAUTIONS

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained





PRODUCT DESCRIPTION

RZR POWER RACER 4T oil is a high performance multi grade and mineral based engine oil specially formulated for all fleet of diesel engine requiring API SL/JASO MA2 Grade its designed for modern diesel engine operating under sever conditions and heavy loads with superb cold start protect on therefore reduces engine wear & tear significantly. The special additives contribute to a significant reductions in engine noise.

Performance level

Meet API SL/JASO MA2 STANDARDS

PRODUCT BENEFITS

- ◆ Provided excellent engine clean in all service conditions.
- ◆ Excellent oxidation & stability to prolong engine oil life.
- ◆ Excellent high sheet temperature stability.
- ◆ Excellent protection against wear and tear
- ◆ Recommended for fleet of diesel engine that coupled with EGR SYSTEM and common raid system for commercial road transport.

TYPICAL APPLICATIONS

RZR POWER RACER 4T is recommended for all types of general applications of automotive and 4STROKE purposes Hero, Honda, Tvs, Bajaj, Yamaha, etc bike segments

KEY FEATURES

1. High water resistance and give excellent service in application where water ingress is unavoidable.
2. High load caring ability
3. Protection against rust and corrosion.

TYPICAL PROPERTIES

| NO | Test parameters | ASTM METHOD |
|----|---------------------------------|-------------|
| 1 | KINEMATIC VISCOSITY SCT @ 100°C | 14.0-15.5 |
| 2 | KINEMATIC VISCOSITY SCT @ 40°C | 124.5 |
| 3 | VISCOSITY INDEX (MIN) | 125 |
| 4 | FLASH POINT °C (MIN) | 220 |
| 5 | POUR POINT °C (MAX) | -24 |
| 6 | DENSITY | 0.885 |
| 7 | TBN -MG KOH/GM | 7.5 -8.5 |

PRECAUTIONS

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained



RZR ZRZR HYDRAULIC OIL AW (32/46/68)



PRODUCT DESCRIPTION

RZR hydraulic Oil 68 AWS(anti wear statics) oil is ideal for all type hydraulic presses CNCS & hydraulic operated cost moving machinery etc. These oils are blend up best quality high viscosity index base.oil & (AW) additives. Product feature

Performance level

Exceeds Denison hf2/hfo, bis-11656-1986

PRODUCT BENEFITS

- Provided excellent engine clean in all service conditions.
- Excellent oxidation & stability to prolong engine oil life.
- Excellent high sheet temperature stability.
- Excellent protection against wear and tear
- Recommended for fleet of diesel engine that coupled with EGR SYSTEM and common raid system for commercial road transport.

TYPICAL APPLICATIONS

HYDRAULIC OIL AW (32/46/68)is recommended for use in manval gear boxes of passenger care, commercial vehicles 4 construction equipments where the higher additive of oil would interfere with gear selection.

KEY FEATURES

1. High water resistance and give excellent service in application where water ingress is unavoidable.
2. High load caring ability
3. Protection against rust and corrosion.

TYPICAL PROPERTIES

| NO | ISOGRADE | 32 | 46 | 68 | 100 | 150 | 220 | 320 |
|----|----------------------------------|-------|-------|-------|-----|------|---------|---------|
| 1 | Kinviscosity _{st} @100c | 5.4 | 6.8 | 8.4 | 11 | 14.8 | 18.8 | 23.4 |
| 2 | Viscosityindex | 100 | 100 | 100 | 98 | 98 | 96 | 96 |
| 3 | Kinviscosity _{st} @ 40c | 30-35 | 43-48 | 64-73 | 100 | 145 | 209 | 304 |
| 4 | Flashpoint(ccc)'cmin | 210 | 215 | 220 | 220 | 230 | 271/520 | 277/531 |
| 5 | Pourpoint'cmax | -20 | -15 | -9 | -6 | -6 | -12 | -12 |

PRECAUTIONS

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained

PACKING SIZE : 210 LTR, 55LTR, 20LTR, 10LTR, 7.5LTR, 5LTR, 1LTR





PRODUCT DESCRIPTION

RZR TURBO PLUS PREMIUM is a high performance multi grade and mineral based engine oil specially formulated for all fleet of diesel engine requiring API-CI-4 Grade its designed for modern diesel engine operating under sever conditions and heavy loads with superb cold start protect on therefore reduces engine wear & tear significantly. The special additives contribute to a significant reductions in engine noise..

Performance level

Meet API CI-4

PRODUCT BENEFITS

- ◆ Provided excellent engine clean in all service conditions.
- ◆ Excellent oxidation & stability to prolong engine oil life.
- ◆ Excellent high sheet temperature stability.
- ◆ Excellent protection against wear and tear
- ◆ Recommended for fleet of diesel engine that coupled with EGR SYSTEM and common raid system for commercial road transport.

TYPICAL APPLICATIONS

RZR TURBO PLUS PREMIUM is recommended for all types of general applications of automotive and industrial purposes

KEY FEATURES

1. High water resistance and give excellent service in application where water ingress is unavoidable.
2. High load caring ability
3. Protection against rust and corrosion.

TYPICAL PROPERTIES

| NO | Test parameters | ASTMMETHOD |
|----|---------------------------------|------------|
| 1 | KINEMATIC VISCOSITY SCT @ 100'C | 14.0-15.5 |
| 2 | KINEMATIC VISCOSITY SCT @ 40'C | 115 |
| 3 | VISCOSITY INDEX (MIN) | 135 |
| 4 | FLASH POINT 'C(MIN) | 220 |
| 5 | POUR POINT 'C(MAX) | -24 |
| 6 | TBN-MG KOH/GM | 7.5 -8.5 |

PRECAUTIONS

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained





PRODUCT DESCRIPTION

RZR EP-90 GEAR CARE premium quality extreme pressure gear lubricating oils solvent refined having high viscosity index with extremely good oxidation stability. These oils are blended with selected extreme pressure additives to anti form anti wear and anti rust properties.

Performance level

A.MEET (EP-TYPE-GL4) IS-1118-1992 B. USMILITARY –MIL-L210

PRODUCT BENEFITS

- Provided excellent engine clean in all service conditions.
- Excellent oxidation & stability to prolong engine oil life.
- Excellent high sheet temperature stability.
- Excellent protection against wear and tear
- Recommended for fleet of diesel engine that coupled with EGR SYSTEM and common rail system for commercial road transport.

TYPICAL APPLICATIONS

RZR EP-90 is recommended for use in manual gear boxes of passenger care, commercial vehicles & construction equipments where the higher additive of a GL-5 oil would interfere with gear selection.

KEY FEATURES

1. High water resistance and give excellent service in application where water ingress is unavoidable.
2. High load carrying ability
3. Protection against rust and corrosion.

TYPICAL PROPERTIES

| NO | Test parameters | ASTM METHOD |
|----|-------------------------------|-------------|
| 1 | Kin viscosity cSt@100°C | 16 -17 |
| 2 | Viscosity index | 90 |
| 3 | Kin viscosity cSt -40°C | 135 |
| 4 | Flash point (CoC)°C min | 220 |
| 5 | Pour point °C max | -9 |
| 6 | Copper corrosion @ 100°C/3hrs | 10 |

PRECAUTIONS

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained





PRODUCT DESCRIPTION

RZR MULTIGRADE ENGINE OIL 20W40 PREMIUM is a high performance multi grade and mineral based engine oil specially formulated for all fleet of diesel engine requiring API-SF/CF Grade its designed for modern diesel engine operating under severe conditions and heavy loads with superb cold start protection therefore reduces engine wear & tear significantly. The special additives contribute to a significant reduction in engine noise..

Performance level

Meet API SF/CF

PRODUCT BENEFITS

- Provided excellent engine clean in all service conditions.
- Excellent oxidation & stability to prolong engine oil life.
- Excellent high shear temperature stability.
- Excellent protection against wear and tear
- Recommended for fleet of diesel engine that coupled with EGR SYSTEM and common rail system for commercial road transport.

TYPICAL APPLICATIONS

RZR MULTIGRADE ENGINE OIL 20W40 PREMIUM is recommended for all types of general applications of automotive and industrial purposes

KEY FEATURES

1. High water resistance and give excellent service in application where water ingress is unavoidable.
2. High load carrying ability
3. Protection against rust and corrosion.

TYPICAL PROPERTIES

| NO | Test parameters | ASTM METHOD |
|----|---------------------------------|-------------|
| 1 | KINEMATIC VISCOSITY SCT @ 100°C | 14.015.5 |
| 2 | KINEMATIC VISCOSITY SCT @ 40°C | 115 |
| 3 | VISCOSITY INDEX (MIN) | 135 |
| 4 | FLASH POINT °C (MIN) | 220 |
| 5 | POUR POINT °C (MAX) | -24 |
| 6 | TBN MG KOH/GM | 7.5-8.5 |

PRECAUTIONS

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained



PACKING SIZE : 210 LTR, 55LTR, 20LTR, 10LTR, 7.5LTR, 5LTR, 1LTR



PRODUCT DESCRIPTION

RZR CNG SPECIAL 20W50 is a high performance multi grade and mineral based engine oil specially formulated for all fleet of diesel engine requiring API-SL Grade its designed for modern diesel engine operating under sever conditions and heavy loads with superb cold start protect on therefore reduces engine wear & tear significantly. The special additives contribute to a significant reductions in engine noise..

Performance level

Meet API SL

PRODUCT BENEFITS

- ◆ Provided excellent engine clean in all service conditions.
- ◆ Excellent oxidation & stability to prolong engine oil life.
- ◆ Excellent high sheet temperature stability.
- ◆ Excellent protection against wear and tear
- ◆ Recommended for fleet of diesel engine that coupled with EGR SYSTEM and common raid system for commercial road transport.

TYPICAL APPLICATIONS

RZR CNG SPECIAL 20W50 is recommended for all types of general applications of automotive and industrial purposes

KEY FEATURES

1. High water resistance and give excellent service in application where water ingress is unavoidable.
2. High load caring ability
3. Protection against rust and corrosion.

TYPICAL PROPERTIES

| NO | Test parameters | ASTM METHOD |
|----|--------------------------------|-------------|
| 1 | KINEMATIC VISCOSITY SCT @ 100 | 14.015.5 |
| 2 | KINEMATIC VISCOSITY SCT @ 40'C | 115 |
| 3 | VISCOSITY INDEX (MIN) | 135 |
| 4 | FLASH POINT 'C (MIN) | 220 |
| 5 | POUR POINT 'C (MAX) | -24 |
| 6 | TBNMG KOH/GM | 7.5-8.5 |

PRECAUTIONS

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained



PACKING SIZE : 210 LTR, 55LTR, 20LTR, 10LTR, 7.5LTR, 5LTR, 1LTR



RZR N ZRZR OIL INDUSTRY PVT. LTD

Head Office:

**501, A. PINNACLE CORPORATE PARK, 5TH FLOOR, BKC, BANDRA (EAST) KOLE KALYAN,
NEARTRADE CENTERE, BANDRA MUMBAI, 4000051, MAHARASTRA, INDIA
CUSTOMERS CARE CELL +91 7719509118, ANY INQUIRY CALL @ +91 7047724252**